

PROFESSIONAL

STAGE MICROPHONES

MICROPHONES



AVL1004

Dimension: $\phi 52 \times 170$ r



AVL1012

Dimension: $\phi 54 \times 158.5$ mm



AVL191D

Dimension: $\phi 52 \times 164$ mm



AVL1960

Dimension: $\phi 52 \times 169$ mm



AVL1000

Dimension: $\phi 54 \times 156.7$ mm



AVL1700

Dimension: $\phi 53.6 \times 170.8$ mm



AVL1300

Dimension: $\phi 42 \times 171.5$ mm





AVL1962

Dimension: $\phi 53.5 \times 161.45$ mm

PROFESSIONAL STAGE MICROPHONES

SPECIFICATION

Elements : Moving Coil Dynamic
Polar Pattern : Cardioid
Frequency : 70-14,000 Hz
Sensitivity : $-75\text{dB} \pm 3\text{dB}$
(0dB=1ubar @1KHz)
Impedance : $500\Omega \pm 30\%$ (@ 1KHz)
Connector : XLR (male)



AVL1900

Dimension: $\phi 51 \times 164.5$ mm



AVL1400

Dimension: $\phi 54 \times 167$ mm



AVL1301

Dimension: $\phi 51 \times 161.45$ mm