


PROJECT 640

LOUDSPEAKER CABINETS

PROJECT

LOUDSPEAKER CABINETS



Grey RAL 7035 or black RAL 9005

ABS loudspeaker

- Bracket included
- 2 way bass reflex
- 6.5" woofer and 1" tweeter
- 100V line transformer(multi Tapp)
- Frequency response @-10dB 70Hz-20kHz
- Dispersion HxV 90°x90°
- High-pass filter recommended 40Hz-24dB/oct
- 4-piece multiple packing
- 40W/80W nominal/maximum power
- Setting 10/20/30/40/8ohm
- Sensitivity 89dB
- Max SPL 108dB



Project 640 WT



Project 640 BT



Wall bracket manufactured from die-cast aluminium with ball/socket multi angle adjustment capability and steel security cable.

Project 640 BT / WT

Code	29227 / 29226
Configuration	2 way
Recommended amplifier	80W rms
Long term power	40W
Short term power	160W
Line transformer (100V)	10-20-30-40W
Nominal impedance	8ohm
Frequency response @-10dB	70Hz-20kHz
Low frequency woofer	165mm
Tweeter	25mm
Sensitivity (@1W,1m)	89dB
Max. Spl	108dB
Dispersion	90x90 HxV
Recommended hp filter	40Hz-24dB/oct
Input connector	Euroblock
Dimensions (WxHxD)	218x312x219mm