FBT Products

Verve Series – Sub-Woofer System Verve 15S - 700W 4 Ohm - 126dB SPL Sub-woofer System



Features:

- Vented bass-reflex system
- custom 15" neodymium long excursion subwoofer
- 13-ply birch cabinet with
- 3 x M10 suspension points

Thick and punchy bass to the music program down to 40Hz. More power and less weight: the FBT VERVE 15S can be used in blocks of two or more for astounding sub bass output level

Verve 15S - 700W 4 Ohm - 126dB SPL Sub-woofer System

Specifications:

| Model | | VERVE 15S |
|------------------------|-------|-------------------|
| Configuration | way | 1 |
| Recommended amplifier | W rms | 700 |
| Nominal impedance | Ohm | 4 |
| Frequency response | @-6dB | 40hz - 200Khz |
| Low frequency woofer | mm | 1x380 (75 ø coil) |
| | inch | 1x15 - (3 ø coil) |
| High frequency driver | mm | - |
| | inch | - |
| Sensitivity (@1W/1m) | dB | 97,5 |
| Maximum SPL | dB | 126 |
| Dispersion | HxV | omni-directional |
| Crossover frequency | kHz | 100 external |
| Input connectors | | 2 x Neutrik® |
| | | Speakon® NL-4 |
| Net dimensions (WxHxD) | mm | 432x540x550 |
| | inch | 17.00x21.26x21.65 |
| Net weight | kg | 28 |
| | lb | 61.73 |