

MIPRO PRODUCTS - MA-708 Wireless Portable PA System



Features:

- Lightweight, extremely rugged design delivering a 120-watt RMS clear and powerful sound for crowds up to 1,000.
- High-efficiency class-D amplifier drive 1" titanium compression driver and 8" woofer speakers.
- Retractable handle and sturdy wheels for easy transport.
- New innovative "digital master volume control" feature enables volume loudness be manually or remotely controlled by a MIPRO 3Ha Handheld Transmitter Microphone instead of a separate remote.
- Up to 4 diversity UHF wireless receivers.
- Industry's easiest and fastest channel set-up using MIPRO AutoScan and ACT technology.
- Industry's only MTM-90 wireless interlinking transmitter option to interlink multiple MIPRO MA-708 portables wirelessly to extend transmission range and expand coverage.
- Weighs only 16kg/35 lbs – loaded.
- Active limiter – keeps sounds clean when driven hard.
- A voice priority feature that mutes the music when mic is used.
- Echo effect control so singers sound fuller and richer.
- A smart 4-segment battery meter for accurate battery reading and charging status.
- Up to 7 hours continuous use per battery charge or plug it in for continuous use.
- External speaker output powers a passive extension speaker.
- XLR & 6.3mm (1/4") microphone inputs with individual volume control.
- Line-in for audio playing / Line-out for external recording.
- Built-in storage compartments for 2 transmitters.
- 3 power modes: AC, rechargeable battery and direct DC.

MIPRO PRODUCTS - MA-708 Wireless Portable PA System

Specifications:

Power Output	120W(rms)/4Ω
T.H.D.	<1%
Frequency Response	50Hz~18KHz±3dB
Speaker	1" horn tweeter, 8" woofer
Crossover network	2.8KHz, -12dB/Oct
Audio Inputs	2 combo microphone jacks. RCA jack Line-input. Separate gain controls.
Audio Outputs	1 REC output, RCA jacks.
Operation Mode	Direct operation on PA system
CD/MP3 Player	Optional
Wireless Receiver	UHF 16 switchable channels. AutoScan and ACT technology
Wireless Microphones	Optional
Frequency Range	620~958MHz
Bandwidth	24MHz
Preset Channels	16 non-interfering channels
Antennas	Integrated
Power Supply	Built-in 12V/4.5AH rechargeable battery x 2 & 18V DC / 100~240V AC switching power supply.
Rechargeable	Built-in intelligent battery system
Charging & Operating Time	8 Hours (automatic charging system) for 6~8 hours operation
Dimensions	336(W)×545(H)×325(D)mm / 13.2(W)×21.5(H)×12.8(D)"
Weight	16.3kg / 35.9lbs
Note	Varied specifications on carrier frequency range, maximum deviation, RF output power and spurious emission to comply regulation of different countries.

Accessories:



MB-70



MS-70



CDM-2



MRM-70