

CSL 630 TIC

CSL 840 TIC




BUILT-IN SPEAKERS

ABS in-ceiling speaker with metal protection grille

- Metal back cover
- Colour white RAL9016,
- Coaxial loudspeaker with 6" woofer and 1/2" tweeter
- Nominal Power 3.8/7.5/15/30W/80hm with 100V/70V line transformer
- 90-20,000Hz frequency response
- 88dB+/- 3dB sensitivity @1W/1m
- Diameter 230x150mm
- Building-in hole 200mm

ABS in-ceiling speaker with metal protection grille

- Colour white RAL9016
- Full range 2.5" dual cone,
- Nominal Power 5/10/20/40W/8ohm with 100V/70V line transformer
- 50-20,000Hz frequency response
- 87dB+/- 3dB sensitivity @1W/1m
- Diameter 100x80mm
- Building-in hole 950mm



	CSL 630 TIC	CSL 840 TIC
Code	29417	29418
Rated/Maximum power	3.8/7.5/15/30W/80hm	5/10/20/40W/8ohm
Frequency response	90-20.000Hz	50-20.000Hz
Sensitivity 1W/1m	88dB	88dB
Input voltage	100V	100V
Cut-out diameter	200mm	240mm
Weight	2,3 Kg	3,1 Kg
Dimensions	ø 230x150mm	ø 270x185mm