MA-100SB Personal Wireless PA System

Introduction

MA-100SB is an all new, ultra compact and ultra-light wireless PA system. The MA-100 is powerful and offers a vast array of features in an easy-to-use package. It can be easily carried via the padded shoulder strap, built-in handle, or mounted on a microphone stand. It is an excellent public address solution for small crowds.

Ideal applications include: School classrooms, Places of worship, Presentations, seminars and meetings, Day-care activities, playground duty, Indoor/outdoor gatherings, Tour guides & Paging, Fire fighters, law enforcement, search & rescue squads, Street performers, Factory and company tours.

Key Features

- Rugged yet lightweight one-piece molded cabinet
- Built-in 1 wireless receiver with 16 auto-scannable frequencies
- Built-in USB music player & recorder with LCD screen
- Built-in one-button alarm/siren for warning of threats
- User-friendly control panel provides intuitive easy operation
- High efficiency class-D amplifier drives a full-range speaker
 AC and lithium responses by bettery experiment
- AC and lithium rechargeable battery operation
- Switching power supply efficiently provides a regulated output voltage
- Available in black or white color

Transmitters & Microphones

ACT-32H	Handheld Transmitter
ACT-32HC	Rechargeable Handheld Transmitter
ACT-32T	Bodypack Transmitter
ACT-32TC	Rechargeable Bodypack Transmitter
MM-107	Supercardioid Dynamic Microphone

Accessories


MB-10	Lithium Rechargeable Battery. (14.8 V / 2.6 AH)
SC-10	Storage and Carry Bag
MS-30	Tripod Microphone Stand

Technical Specifications

Portable PA		
Max. Power Output	50 Watts	
Amplifier	Class D	
Sensitivity	Typical: 90 dB Maximum: 102 dB	
T.H.D.	< 1%	
Frequency Response	50 Hz – 18 kHz	
Loudspeaker	5" full-range high efficiency	
Audio Inputs	Wired: 6.3 mm (1/4")	
Addio Inputs	Line-In: 3.5 mm (1/8")	
Bluetooth Connectivity	Yes	
Audio Output	3.5 mm (1/8")	
Alarm Siren	Siren sound with fade-in mode	
Installation	Microphone stand, table mounted, shoulder belt.	
	AC: External 100–240V AC switching power supply (Max. Power	
Power Supply	Consumption: 60 W)	
	DC & Battery: 14.8V / 2.6AH rechargeable lithium battery (MB-10×1)	
Charge Time	Up to 4 hours (automatic charging management)	
Standby Time	Up to 12 hours	
Battery Indicator	4-level indicator (25/50/75/100%)	
Dimensions (W×H×D)	135 × 144 × 240 mm / 5.3 × 5.6 × 9.4 "	
Weight	Approx. 1.8 kg / 3.9 lbs (MB-10 battery included)	
Color	Black or white option	
	Wireless System	
Receiver Channel	Single	
Frequency Range	UHF 480 – 934 MHz (country dependent)	
Bandwidth	24 MHz	
Preset Channels	16	
Channel Set-up	Scan & ACT sync	
Antenna	Built-in	
	Audio Player	
Built-in USB Port	USB 2.0	
USB Play & Record	LCD displays track name, number, time, recording status.	
Operation	On-board. USB remote control included.	









MIPRO Electronics Co., Ltd Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan Tel: +886.5.238.0809 | Fax: +886.5.238.0803 www.mipro.com.tw | mipro@mipro.com.tw

MA-100DB Personal Wireless PA System

Introduction

MA-100DB is an all new, ultra compact and ultra-light wireless PA system. The MA-100 is powerful and offers a vast array of features in an easy-to-use package. It can be easily carried via the padded shoulder strap, built-in handle, or mounted on a microphone stand. It is an excellent public address solution for small crowds.

Ideal applications include: School classrooms, Places of worship, Presentations, seminars and meetings, Day-care activities, playground duty, Indoor/outdoor gatherings, Tour guides & Paging, Fire fighters, law enforcement, search & rescue squads, Street performers, Factory and company tours.

Key Features

- Rugged yet lightweight one-piece molded cabinet
- Built-in 2 wireless receivers with 16 auto-scannable frequencies
- Built-in USB music player & recorder with LCD screen
- Built-in one-button alarm/siren for warning of threats
- User-friendly control panel provides intuitive easy operation
- High efficiency class-D amplifier drives a full-range speaker
 AC and lithium responses by bettery experiment
- AC and lithium rechargeable battery operation
- Switching power supply efficiently provides a regulated output voltage
- Available in black or white color

Transmitters & Microphones

ACT-32H	Handheld Transmitter
ACT-32HC	Rechargeable Handheld Transmitter
ACT-32T	Bodypack Transmitter
ACT-32TC	Rechargeable Bodypack Transmitter
MM-107	Supercardioid Dynamic Microphone

Accessories


MB-10	Lithium Rechargeable Battery. (14.8 V / 2.6 AH)
SC-10	Storage and Carry Bag
MS-30	Tripod Microphone Stand

Technical Specifications

Portable PA		
Max. Power Output	50 Watts	
Amplifier	Class D	
Sensitivity	Typical: 90 dB Maximum: 102 dB	
T.H.D.	< 1%	
Frequency Response	50 Hz – 18 kHz	
Loudspeaker	5" full-range high efficiency	
Audio Inputs	Wired: 6.3 mm (1/4")	
Addio inputs	Line-In: 3.5 mm (1/8")	
Bluetooth Connectivity	Yes	
Audio Output	3.5 mm (1/8")	
Alarm Siren	Siren sound with fade-in mode	
Installation	Microphone stand, table mounted, shoulder belt.	
	AC: External 100–240V AC switching power supply (Max. Power	
Power Supply	Consumption: 60 W)	
	DC & Battery: 14.8V / 2.6AH rechargeable lithium battery (MB-10×1)	
Charge Time	Up to 4 hours (automatic charging management)	
Standby Time	Up to 10 hours	
Battery Indicator	4-level indicator (25/50/75/100%)	
Dimensions (W×H×D)	135 × 144 × 240 mm / 5.3 × 5.6 × 9.4 "	
Weight	Approx. 1.9 kg / 4.1 lbs (MB-10 battery included)	
Color	Black or white option	
	Wireless System	
Receiver Channel	Dual	
Frequency Range	UHF 480 – 934 MHz (country dependent)	
Bandwidth	24 MHz	
Preset Channels	16	
Channel Set-up	Scan & ACT sync	
Antenna	Built-in	
	Audio Player	
Built-in USB Port	USB 2.0	
USBPlay & Record	LCD displays track name, number, time, recording status.	
Operation	On-board. USB remote control included.	









MIPRO Electronics Co., Ltd Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan Tel: +886.5.238.0809 | Fax: +886.5.238.0803 www.mipro.com.tw | mipro@mipro.com.tw